

HDCB-1080-312MP

2.0 Megapixel Starlight HD-over-Coax Bullet



Features

- 1/2.8" STARVIS CMOS
- 30fps @ 1080P / 720P
- High speed, long distance real-time transmission
- OSD Menu, Control over Coaxial Cable
- Day/Night (ICR), AWB, AGC, BLC, 3D-DNR
- 2.7 ~ 13.5mm Varifocal Lens
- Motorized Zoom
- Max. IR LEDs length 196ft , Smart IR, True WDR
- IP67, DC12V



Specifications

| | | HDCB-1080-312MP |
|---------------------------------|--------------|---|
| Image Sensor | | 1/2.8" STARVIS CMOS |
| Resolution | HD-over-Coax | 1937 x 1097 |
| Frame Rate | | 30fps @ 1080P; 30fps @ 720P |
| Electronic Shutter | | 1/3 ~ 1/100,000s |
| Effective Picture (H x V) | | 1937 x 1097 |
| Video Output | | 1 x BNC - HD |
| Focal Length | | 2.7 ~ 13.5mm |
| Lens Type | | Varifocal / Motorized Zoom |
| Min. Illumination Color / B&W | | 0.005 Lux @ F1.3 (0 Lux IR LED on) |
| Infrared Range | | 197ft. (Max.) |
| Day / Night | | Auto (ICR) / Manual |
| Noise Reduction | | 3D |
| OSD Menu | | Supported |
| Angle of View | | H: 102°~29° |
| Close Focus Distance | | 7.87" |
| DORI | Detect | 154ft / 502ft |
| | Observe | 62ft / 200ft |
| Wide / Tele | Recognize | 30ft / 102ft |
| | Identify | 16ft / 49ft |
| WDR Type | | True Wide Dynamic Range |
| Weatherproof Rating | | IP67 |
| Transmission Distance | | Over 1,640ft (500m) via 75-3 coaxial cable |
| Bracket Included | | No |
| Power Supply / Consumption | | 12V±10% DC / 10.1W |
| Working Environment | | -40°F ~ 140°F, less than 95% RH (no condensation) |
| Dimensions / Weight | | 8.39"×3.56"×3.56" / Approx. 1.7 lbs |