

## KCIAD2MV

1080P IR HD-over-Coax Dual Voltage Varifocal Armor Dome



### Features

- 1/3" 2.0 Megapixel / 1080P Sony CMOS
- 30 fps @ 1080P, 25/30/50/60 fps @ 720P
- 2 Pipe Fitting Options
- High speed, long distance real-time transmission
- OSD Menu
- Day/Night (ICR), 3D DNR, D-WDR
- 2.8mm ~12mm DC Auto Iris lens
- Max. IR LEDs length 65ft (20m), Smart IR
- IP66, DC12V / AC24V
- 3 Axis Gimbal



Model	KCIAD2MV
Image Sensor	1/3" 2.0 Megapixel Sony CMOS
Effective Picture	1920 x 1080
Electronic Shutter	Auto / Manual
Resolution	HD-over-Coax: 1080P @ 30fps / 720P @ 60fps
Min. Illumination	1.0 Lux
IR LEDs	30 IR LEDs
Max IR Length	65ft
S/N Ratio	> 52dB (AGC off)
Video	Digital: 1080P / 720P
Brightness	0~20
Lens	DC (ALC) / Manual (ELC)
Sens Up	Auto / Off
AGC	0~20
Defog	On / Off
Backlight	Off / HLC / BLC / WDR
Day & Night	Auto / color / B&W / Ext
White Balance	Auto / Autoext / Preset / Manual
DNR	Low / Middle / High
Sharpness	0~10
Mirror	On / Off
Flip	On / Off
Shading	On / Off
Privacy Mask	On / Off
Motion Detection	On / Off
Output Mode	Analog / HD-over-Coax
CVBS	NTSC / PAL
Power Supply (Not Included)	DC 12V / AC24V 110mA (CDS on: 440mA) ±10%
Weatherproof Rating	IP66
Working Environment	-22°F ~ 140°F (-30°C ~ 60°C) / Less than 80% RH (no condensation)
Dimensions (H × W × D) / Weight	2.5" × 6" × 6" / Approx. 2lbs
Warranty	1 Year