

OVPOE4-60

4 Port PoE Switch

Features

- 4 PoE ports, 10/100 mbps each port
- 2 Gigabit Uplink ports for high speed connection
- Standard compliant IEEE802.3af
- Support 10/100Mbps fast Ethernet
- Data transmission up to 100 meters
- Support power up to 15.4W per each port
- LED indicators show working status of LAN and power
- Anti-Static and Circuit Isolation protection via Anti-Lighting Chip design
- Easy installation and use , no need to convert by software and network protocol



Model	OVPOE4-60
Network Ports	4 x 100M bit Auto-MDIX PoE / PoE+ RJ-45 ports 2 x 10/100/1000M Gigabit copper RJ45 ports (MDI / MDIX adaptive)
Speed	10/100 Mbps (Half / Full Duplex)
Forwarding Rate	100 Mbps / 148,800 pps, 10 Mbps / 14,880 pps
Data RAM Buffer	96 kb
Address Table	2 K MAC entries
Switch Fabric	1Gbps
Network Standard	IEEE 802.3 10Base-T IEEE 802.3u 100Base-TX IEEE 802.3ab 1000Base-T IEEE 802.3af Power over Ethernet (PoE) IEEE 802.3x Flow Control
Power	100-240 V, 50/60 Hz, 1.5A
Diagnostic LEDs	Power / PoE / Link / Activity
Power Consumption	Min: 8 Watts (standby) Max: 72 Watts PoE Max: 60 Watts (4 x 15 watts PoE devices connected)
Temperature	Operating: 32° ~ 113° F (0° ~ 45° C) Storage: -4° ~ 194° F (-20° ~ 90° C)
Humidity	10% - 90% (non-condensing)
Dimensions	5.5" x 3.6" x 1.1" (140 x 91 x 28 mm)
Weight	1.9 lbs (0.85 kg)
Certifications	CE, FCC ROHS
Safe Standard	CE/LVD
Power Over Ethernet	Up to 15.4 watts for PoE PoE: pin 3,6 for power- and pin 1,2 for power+