

OVPOE8-150

8 Port PoE Switch

Features

- Standard compliant IEEE802.3af
- Support 10/100Mbps fast Ethernet
- Data transmission up to 100 meters
- Support power up to 15.4W per each port
- LED indicators show working status of LAN and power
- Anti-Static and Circuit Isolation protection



Model	OVPOE-8-150
Network Ports	8 x 10/100Mbps PoE Port
Speed	100M/1000Mbps Full Duplex
Function Standard	Bandwith: 3.6Gbps Network Delay (10~100Mbps): Max 20 microseconds Packet Buffer Memory: 96KB Database Size: 1,024 MAC address 1000Mbps / 148,800pps, 100Mbps / 148,000pps, 10Mbps / 14,880pps
Network Standard	IEEE 802.3i 10BASE-T IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3x Flow Control IEEE 802.3af Power over Ethernet
Power	Built-in 250W power adapter
Diagnostic LEDs	Power / PoE / Link / Activity
Power Consumption	Min: 8 Watts (standby) Max: 72 Watts PoE Max: 60 Watts (4 x 15 watts PoE devices connected)
Temperature	Operating: 32° - 104° F (0° - 40° C) Storage: -4° ~ 194° F (-20° ~ 90° C)
Humidity	10% - 90% (non-condensing)
Dimensions	17.3" x 7" x 1.4" (440 x 180 x 35 mm) /□1 U)
Weight	4.4 lbs (2 kg)
Certifications	CE, FCC, ROHS
Safe Standard	CE/LVD