



# OVPOE24-370-2GC

24 Port + 2GB Uplink 370W PoE Switch 10 / 100 Base-TX

POWER	
Power Supply	External Power Adaptor
Voltage Range	AC115~230V
Switch Consumption	<15W

ETHERNET	
Speed	1~24 Port : 10/100Mbps
	G1~G2: Gigabit Combo
Transmission Distance	328ft for RJ-45
	2Km 20Km for SFP Port The Optical module is optional

NETWORK SWITCH	
Ethernet Standard	IEEE 802.3/802.3u/802.3ab/802.3af/at
Switching Capacity	8.8G
Transfer Rate	14,880pps for 10Mbps
	148,800pps for 100Mbps
	1,488,000pps for 1000Mbps
MAC Address	4K MAC address table

LINK	
On / Green	The port is connecting
Blinks	The port is receiving or transmitting data
Off	The port is not linked successfully with the device
On / Orange	PD is connected
Off	No PD is connected or power forwarding fails
Total Output Capacity	370W
Output Capacity per Port	Up to 30W per port
PoE Pin Assignment	V+(RJ45 Pin 1,2), V-(RJ45 Pin 3,6)

GENERAL	
Working Temperature	0~40 °C
Storage Temperature	-40~70 °C
Humidity	0~90% (Non-Condensing)
Dimensions	17.3" x 7.9" x 1.7"



**OVPOE4G**  
4+1 Port 60W PoE  
Switch 10 / 100 / 1000



**OVPOE8-125**  
8 Port PoE Switch 10 /  
100 / 1000 Base-TX



**OVPOE16-250**  
16 Port PoE + 2GB Switch  
10 / 100 / 1000 Base-TX



**OVPOE24X-400-2GC**  
24 Port PoE + 2GB Switch  
10 / 100 / 1000 Base-TX



**CAT6-100**  
100FT CAT6 Ethernet  
Cable