


Optiview



OVPOE8-125V

8 + 1 Port 125W PoE Switch 10 / 100 / 1000 with 1x SFP



8x RJ45 Ports

Get high speed data transfer rates easily by connecting up to 5x Cat5e or Cat6 UTP cables.

SFP

1x SFP Port

Provide flexible fiber connectivity easily with extremely high speeds with low loss in a compact design.



10/100/1000

Utilizing auto-negotiation, this switch detects cable type, power needs, and automatically selects the best speed.



Up to 125 Watts

Provides up to 125 watts of Power over Ethernet budget for all connected devices.



Commercial Grade

Built for endurance, the OVPOE8-125V is constructed out of a durable metal housing.

FEATURES

- Gigabit PoE switch conforms to IEEE802.3af/at standards.
- 10 ports switch with each 10/100/1000Base-TX ports.
- Circuit protection prevents power interference between ports
- Remote power feeding up to 100m
- PoE switch support CCTV, desktop size and wall-mount design
- Provides 8 PoE injector and 125W power adapter
- High back-plane bandwidth 20Gbps

SPECIFICATIONS

Power Supply	External Power Adaptor
Voltage Range	DC48V- 57V
Consumption	<6W
Speed	1-8 Port : 10/100/1 000Mbps 1TP + 1 SFP Uplink : 1 000Mbps
Ethernet Standard	IEEE 802.3x IEEE 802.3 802.3u 802.3ab 802.3af/at
Switching capacity	20G
Transfer Rate	14,880pps for 10M bps 148,800pps for 1 00Mbps 1,488,000pps for 1 000Mbps
MAC Address	4K MAC address table
LINK/ACT	On / Green: The port is connecting Blinks: The port is receiving or transmitting data Off: The port is not linked successfully with the device

OVPOE8-125V

9 + 1 Port 125W PoE Switch 10 / 100 / 1000



PRODUCT SPECIFICATIONS

SPECIFICATIONS CONT.	
POE	On / Orange: PD is connected Off: No PD is connected or power forwarding fails Capacity: 119W
Environment	Temperature: 32.0-104.0°F Storage: 40.0°F-158.0°F
Mechanical	Dimension: 8.58" x 4.21" x 1.14" Color: Gray