



130 dB Outdoor IP Speaker w/ Two-Way Talk

SKU: IPSPKR-30-NCV

- PoE
- Custom and Prerecorded Audio files
- Built-in mic for Two-Way Talk
- Easy Setup & Configuration
- Remote use w/ Surveillance Trailers & NVRs
- IP66



Product Specifications

SPEAKER	
Rated Power	30 W
Max. Acoustic Pressure	130 dB SPL
Frequency Response	300 Hz to 12.5 kHz
Impedance	8 Ω

MATERIAL	
Material	ABS Plastic

NETWORK	
Network Protocol	IPv4, HTTP, HTTPS, SSL/TLS, DNS, TCP, UDP, DHCP, UPnP, ARP, SSH
Interface Protocol (API)	ONVIF, RTSP, RTP, LAPI
Browser	Firefox 87+, Chrome 90+, Edge 90+, Safari 17+

BUILT IN MIC	
Amount	1
Frequency Response	100 Hz to 8 kHz
Sensitivity	-37 dBV/Pa
Sampling Rate	8 kHz
Quantization Bits	16 bit

AUDIO	
Broadcast	Regular Broadcast, Live Broadcast, Alarm Broadcast
Two-Way Audio	Support
Audio Compression	G.711U
Audio File Format	MP3, WAV
Audio File Size	2 KB ≤ Audio File Size ≤ 10 MB

Spec Sheet: IPSPKR-30-NCV

130 dB Outdoor IP Speaker w/ Two-Way Talk



Product Specifications

LANGUAGE	
Language	38 languages: Simplified Chinese, Traditional Chinese, English, Vietnamese, Thai, Turkish, Spanish (Latin America), Portuguese (Brazil), Spanish, Portuguese, French, German, Italian, Dutch, Polish, Czech, Hungarian, Slovak, Russian, Hebrew, Arabic, Ukrainian, Estonian, Bulgarian, Greek, Romanian, Danish, Swedish, Norwegian, Finnish, Croatian, Slovenia, Serbia, Korean, Japanese, Latvian, Lithuanian, Persian

INTERFACE	
Network Interface	Ultra 265 / H.265 / H.264
Audio In	RCA (only be used for sound amplification, cannot be used for intercom)
Alarm In	2
Power Supply	PoE (IEEE 802.3at), DC 24 V/1.4 A, DC 12 V/2.5 A

CERTIFICATION	
Safety	CE LVD (EN IEC 62368-1: 2020+A11: 2020), UL (UL 62368-1, 3rd Ed., Issue Date: 2019-12-13)
EMC	CE-EMC (EN 55032: 2015 + A1: 2020, EN 61000-3-3: 2013 + A1: 2019, EN IEC 61000-3-2: 2019 + A1: 2021, EN 55035: 2017 + A1: 2020), FCC (FCC CFR 47 part15 B, ANSI C63.4-2014)
Environment	CE-RoHS (2011/65/EU; (EU) 2015/863); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006)

COMPLIANCE	
NDAA Compliant	Support

WORKING ENVIRONMENT	
Working Temperature	-22 °F to 131 °F
Working Humidity	≤ 90% RH (non-condensing)

DIMENSIONS	
Dimensions	11.1"×8.1"×11.2"

APPROVAL	
Protection	IP66

Additional Products



OPTIVIEW'S VIDEO MONITORING SOFTWARE
Remote Monitoring



NVR8P8-2B-NCV
16MP 8 Channel 8 PoE 1U NVR with Analytics



AL2000
Compact Smart Solar Trailer – DOT Approved



AL3000
Mid-Size Smart Solar Trailer – DOT Approved



AL4000
Heavy-Duty Smart Solar Trailer – DOT Approved

Spec Sheet: IPSPKR-30-NCV

130 dB Outdoor IP Speaker w/ Two-Way Talk



Dimensions

